

AD 734383

NOLTR 71-216

CONCENTRATION OF BROMIDE IONS IN
SEAWATER BY ISOTOPIC EXCHANGE

By
Stephen C. Fott

8 NOVEMBER 1971

NOL

NAVAL ORDNANCE LABORATORY, WHITE OAK, SILVER SPRING, MARYLAND

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED

NOLTR 71-216

Reproduced by
NATIONAL TECHNICAL
INFORMATION SERVICE
Springfield, Va 22151

DDC
RECEIVED
JAN 4 1972
RECEIVED
C

16

**BEST
AVAILABLE COPY**

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R & D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

| | | | |
|---|--|---|---------------------------|
| 1. ORIGINATING ACTIVITY (Corporate author) Naval Ordnance Laboratory White Oak, Silver Spring, Maryland | | 2a. REPORT SECURITY CLASSIFICATION Unclassified | |
| 3. REPORT TITLE Concentration of Bromide Ions in Seawater by Isotopic Exchange | | 2b. GROUP | |
| 4. DESCRIPTIVE NOTES (Type of report and inclusive dates) | | | |
| 5. AUTHOR(S) (First name, middle initial, last name) Stephen C. Foti | | | |
| 6. REPORT DATE 8 November 1971 | | 7a. TOTAL NO. OF PAGES 15 | 7b. NO. OF REFS 12 |
| 8a. CONTRACT OR GRANT NO. | | 8b. ORIGINATOR'S REPORT NUMBER(S) NOL TR 71-216 | |
| 8c. PROJECT NO. NSSC Work Request 10005 of 19 May 1971 pertaining to ARPA Order 1798 of 11 March 1971. | | 8d. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) | |
| 10. DISTRIBUTION STATEMENT Approved for public release; distribution unlimited | | | |
| 11. SUPPLEMENTARY NOTES | | 12. SPONSORING MILITARY ACTIVITY Advanced Research Projects Agency Washington, D.C. | |
| 13. ABSTRACT A study was conducted to determine the feasibility of concentrating radioactive bromide ions in seawater by passing the seawater through a column of silver bromide. The radioactive bromide ions in the seawater are isotopically exchanged with the bromide ions in the silver bromide. The effect of column height, flow-rate, volume and/or residence time of seawater on the amount of bromine exchanged was studied and each of these variables was found to have a significant effect. | | | |

DD FORM 1473

1 NOV 66

(PAGE 1)

S/N 0101-807-6801

UNCLASSIFIED

Security Classification

UNCLASSIFIED

Security Classification

| 14 KEY WORDS | LINK A | | LINK B | | LINK C | |
|--|--------|----|--------|----|--------|----|
| | ROLE | WT | ROLE | WT | ROLE | WT |
| Isotopic Exchange Bromine in Seawater Silver Bromide Bromine Concentration Radioactivity in Seawater | | | | | | |

CONCENTRATION OF BROMIDE IONS IN SEAWATER BY ISOTOPIC EXCHANGE

Prepared by:
Stephen C. Foti

ABSTRACT: A study was conducted to determine the feasibility of concentrating radioactive bromide ions in seawater by passing the seawater through a column of silver bromide. The radioactive bromide ions in the seawater are isotopically exchanged with the bromide ions in the silver bromide. The effect of column height, flow-rate, volume and/or residence time of seawater on the amount of bromine exchanged was studied and each of these variables was found to have a significant effect.

NOT REPRODUCIBLE

CHEMISTRY RESEARCH DEPARTMENT
NUCLEAR CHEMISTRY DIVISION
NAVAL ORDNANCE LABORATORY
SILVER SPRING, MARYLAND

8 November 1971

Concentration of Bromide Ions in Seawater by Isotopic Exchange

There is a need for determining radioactive bromide ions in the ocean. The amount of bromine in seawater is relatively small (65 mg/l), and a substantial improvement in detection sensitivity could be achieved by concentration of the bromine. Required is a fast-reacting, in situ system for concentration capable of accomodating large volumes of seawater.

A preliminary study has been made of isotopic exchange as a possible method for concentrating bromine in seawater. Silver bromide has been used with success in retaining bromide ions from seawater at high flow rates, for large volumes of seawater, and for sufficient lengths of time to permit counting of any radioactive bromine atoms present.

This work has been supported by the Advanced Research Projects Agency, N. C. Work Request 1-0005, 19 May 1971, to NOL pertaining to ARPA Order 1798, 11 March 1971.

The views and conclusions contained in this document should not be interpreted as necessarily representing the official policies, either expressed or implied, of the Advanced Research Projects Agency.

ROBERT WILLIAMSON II
Captain, USN
Commander

Albert Lightbody
ALBERT LIGHTBODY
By direction

CONTENTS

| | Page |
|--------------------|------|
| INTRODUCTION | 1 |
| BACKGROUND | 1 |
| APPROACH | 1 |
| EXPERIMENTAL | 2 |
| Materials | 101 |
| Apparatus | 101 |
| PROCEDURE | 3 |
| RESULTS | 3 |
| CONCLUSION | 3 |
| REFERENCES | 11 |

ILLUSTRATIONS

| Figure | Title | Page |
|--------|--|------|
| 1 | Apparatus used for the isotopic exchange | 3 |
| 2 | Retention of bromide ions in seawater by isotopic exchange in AgBr columns | 6 |

TABLES

| Table | Title | Page |
|-------|--|------|
| 1 | Isotopic Retention of ⁸² Br with Silver Bromide | 7 |
| 2 | Statistical Analysis of the Data | 8 |
| 3 | Description of ⁸² Br from AgBr | 9 |

NOT REPRODUCIBLE

NOT REPRODUCIBLE

INTRODUCTION

A method is required for the in-situ determination of radioactive bromide ions in the ocean. The amount of radioactive bromide ions is expected to be very low and thus sensitive methods of analysis are sought. Several investigators have made low-level determinations of other radionuclides in seawater (1-4) by means of in-situ gamma-ray probes coupled to counters or to pulse-height spectrometers. A substantial improvement in sensitivity could be achieved if the radioactive bromide ions in the seawater were to be concentrated and then counted.

BACKGROUND

Commonly used methods of concentration of radionuclides in seawater are: (1) co-crystallization(5), (2) evaporation or freeze drying(6), (3) co-precipitation(7), (4) solvent extraction(8), (5) ion-exchange(9) and (6) isotopic exchange(10,11). Of these several methods isotopic exchange appears to be the most appropriate for the present application where a fast-reacting, in-situ system is required and large quantities of seawater are involved.

In the isotopic exchange method, as applied to this problem, seawater would be passed through a porous bed containing bromide ions bound into a crystal lattice. Bromide ions in the seawater would exchange with the bromide ions in the bed. In the isotopic exchange process, there appears to be an initial rapid exchange in which the exchanged ion is either retained for a short period and then released by subsequent exchange or retained semi-permanently. Exchange takes place at the surface of the crystal lattice, and the new ion may get buried deep within the lattice as a result of diffusion and/or recrystallization. Koltoff (10) concluded from his studies that recrystallization was the principal mechanism involved in such retention, and Polessitisky (11) and co-workers estimated that the self-diffusion coefficient of Br^- in a silver bromide (AgBr) bed is at least one thousand times too small to account for observed rates of the $\text{AgBr} - \text{Br}^-$ exchange reaction.

APPROACH

Seawater samples containing ^{82}Br were passed through an isotopic exchange bed of AgBr . The amount of ^{82}Br exchanged was determined by gamma counting aliquots of the seawater samples before and after passage through the AgBr column.

A 3 x 3 factorial experiment was set up to study the effect of several variables (factors) on the amount of ^{82}Br exchanged. The factorial experiment is useful in determining whether or not

variations due to factors studied are greater than might be expected from purely random variations, and also in determining whether or not interactions between pairs of factors are significant. The factors studied in this experiment were the following: (1) height of the AgBr column, (2) flow-rate, and (3) residence time (i.e., time duration of flow).

In addition to the factorial experiment, the desorption rate of ^{82}Br from the AgBr column was studied.

EXPERIMENTAL

MATERIALS

1. Silver bromide (Fischer and Baker). The silver bromide was crushed and sieved through a Tyler standard screen. A 12-24 mesh screen (701-1397 microns) was used.
2. Synthetic seawater. Synthetic seawater is made by dissolving simulated sea salt mix, (Lake Product Co. Inc., St. Louis, Mo.) in distilled water. Simulated sea salt mix contains those elements found in natural sea salt in quantities greater than 0.004%.
3. Radioactive bromine. ^{82}Br was obtained by thermal neutron activation of ammonium bromide. A stock solution was made by dissolving the irradiated ammonium bromide in distilled water. An aliquot of the stock solution was added to synthetic sea water and stored in a polyethylene bottle.

APPARATUS

1. Exchange columns. Three columns were made, each consisting of a Pyrex tube (0.77 cm i.d.) with a glass frit on the bottom. The columns were each loaded with a water slurry of AgBr. Column 1 was filled to a height of 1 cm, Column 2 to a height of 3 cm, and Column 3 to a height of 9 cm. The dry weight of AgBr used for each column was 1, 3 and 9 g, respectively.
2. Vacuum pump. A Duo Seal pump was used to draw the seawater through the column into a suction flask attached to the bottom of the column.
3. Vacuum gage. In order to obtain reproducible flow rates, a gage which measures the vacuum in inches of mercury was used. Vacuum was adjusted by bleeding air into the system through a stopcock (see Figure 1).
4. Gamma-ray counter. A sodium iodide [NaI(Tl)] scintillation detector with a well was used. The NaI(Tl) crystal was 3 in. dia. x 3 in. long, and was encased in a lead shield 3 in. thick.

PROCEDURE

Seawater was passed through the isotopic exchange columns at various flow rates. The fraction of the radioactive bromide ions retained on a column was determined by counting an aliquot of the stock synthetic seawater and a similar aliquot of the seawater that had been passed through the column and comparing the two counts.

A series of runs were made on each of the three columns in accordance with the flow-rates and residence times shown in Table 1. The corresponding volume of seawater used in each run is also shown in Table 1.

The rate of desorption of ^{82}Br from AgBr was also studied. For this study, a 9 cm and a 1 cm column, each containing ^{82}Br , were each washed with four 10 ml aliquots of seawater which did not contain ^{82}Br . For these washings, flow rates of 3.73 and 9.07 ml/cm²/sec were used for the 9 cm and the 1 cm columns, respectively. The washes were made in rapid succession.

The apparatus used for these measurements is shown in Figure 1.

RESULTS

The data obtained are shown in Table 1 and the results of the data analysis are shown in Table 2. A description of the statistical treatment of the data obtained in a factorial experiment such as this may be found in standard texts on experimental statistics. The F ratios in Table 2 are the ratios of the "mean square" of a factor (e.g., volume, flow-rate, or amount of AgBr) to the "mean square" of the error. Rather than determine the random error by replication, the error term was determined from the second-order interactions between the three factors. By comparing the F ratios in Table 2 with those tabulated by Fisher and Yates (12) for tests of significance, it is seen that, in the ranges studied, the amount of AgBr, flow-rate, residence time as well as the interactions between these factors all have significant effects on the isotopic exchange of ^{82}Br with AgBr.

The observations in Table 1 are also presented in plotted form in Figure 2. From Figure 2, it can be readily seen that the isotopic exchange of ^{82}Br with AgBr increases with column height, decreases with flow rate, and, to a lesser extent, decreases with residence time.

The data obtained in the desorption study are presented in Table 3. Initially, the radioactive bromide ions are rapidly desorbed, but the rate of desorption diminishes with time.

CONCLUSION

The results obtained indicate that bromide ions in seawater can be concentrated by the technique of isotopic exchange. The AgBr can

concentrate the bromide ions in seawater and the seawater can desorb the bromide ions from the AgBr. Optimization of the concentration system would involve trade-offs between column size, flow-rate and counting procedure. Retention factors of even 20-30% would result in a reduction of detector size required by a factor of approximately 5×10^3 , provided suitable flow-rates through the exchange bed can be achieved, and that the desorption time is not excessive.




FIG. 1 APPARATUS USED FOR THE ISOTOPIC EXCHANGE




FIG. 2 RETENTION OF BROMIDE IONS IN SEAWATER BY ISOTOPIC EXCHANGE IN AgBr COLUMNS

TABLE 1

ISOTOPIC RETENTION OF ^{82}Br WITH SILVER BROMIDE

| Volume (ml) | Residence time (sec) | Bromine Retention (%) | | |
|--|----------------------------|-----------------------|-----------------|-----------------|
| | | Col. 1 (1cm) | Col. 2 (3cm) | Col. 3 (9cm) |
| Flow-rate = 0.37 ml/cm ² /sec | | | | |
| 5 | 30 | 16.0 | 42.4 | 70.3 |
| 15 | 90 | 13.2 | 31.4 | 57.9 |
| 48 | 270 | 11.2 | 26.0 | 50.3 |
| Flow-rate = 0.89 ml/cm ² /sec | | | | |
| 13 | 30 | 10.1 | 24.9 | 46.2 |
| 39 | 90 | 9.3 | 15.4 | 29.3 |
| 115 | 270 | 6.4 | 9.6 | 28.2 |
| Flow-rate = 1.76 ml/cm ² /sec | | | | |
| 25 | 30 | 5.4 | 10.8 | 31.8 |
| 75 | 90 | 5.6 | 10.7 | 24.7 |
| 245 | 270 | 5.3 | 8.0 | 19.3 |

TABLE 2

STATISTICAL ANALYSIS OF THE DATA

| Factors | Degrees of freedom | Sum of squares of deviations | Mean squares | F ratios |
|---------------------------|--------------------|------------------------------|--------------|----------|
| <u>Single Factors</u> | | | | |
| Volume | 2 | 519 | 259 | 61.7 |
| Flow rate | 2 | 2293 | 1146 | 272.8 |
| AgBr | 2 | 4360 | 2180 | 519.0 |
| <u>Interactions</u> | | | | |
| Volume x Flow Rate | 4 | 77 | 19 | 4.5 |
| Volume x AgBr | 4 | 166 | 42 | 9.9 |
| Rate x AgBr | 4 | 569 | 142 | 33.9 |
| Volume x Flow Rate x AgBr | 8 | 34 | 4.2 | |
| (error) | | | | |

TABLE 3

DESORPTION OF ^{82}Br FROM AgBr

| Seawater Washes (10 ml aliquots) | ^{82}Br desorption (%) | |
|-------------------------------------|---------------------------------|------|
| | (9g) | (1g) |
| First | 27.2 | 56.7 |
| Second | 8.1 | 5.7 |
| Third | 2.1 | 1.4 |
| Fourth | 0.9 | 0.7 |

REFERENCES

1. Riel, G. K., "Natural Gamma Spectra Measured Under the Sea," M.S. Thesis, University of Maryland, College Park, 1961.
2. Wesley, E. J., Nyberg, R. A., "Comparison of Cesium Iodide and Sodium Iodide for Underwater Radiation Detection System," U.S. Naval Radiological Defense Laboratory, USNRDL-TR-1012 21 April 1966.
3. Folsom, T. R., "Radiological Techniques and Instruments Used for the Oceanographic Survey on Operation Wigwag," Armed Forces Special Weapons Project, WT-1016, Scripps Institution of Oceanography, 1955.
4. Riel, G. K., "Concentration of Radioisotopes in Environmental Water Measured by Underwater Gamma Spectrometry," U.S. Naval Ordnance Laboratory, NOLTR-66-231, 20 Dec. 1966.
5. Lai, M. G., Weiss, H. V., "Co-crystallization of Ultramicro Quantities of elements with Thionalid; Determination of Silver in Seawater," Anal. Chem. 34:1012, 1962.
6. Schutz, D. F., Turekian, K. K., "The Investigation of the Geographical and Vertical Distribution of Several Trace Elements in Seawater Using Neutron Activation Analysis," Geo-chim. et Cosmochim. Acta 29: 259, 1965.
7. Kopi, J., Hollstein U., "An Improved Method for the Determination of Trace Quantities of Plutonium in Aqueous Media," Health Physics 8:41, 1962.
8. West, T. S., "Separation of Traces of Inorganic Ions from Aqueous Solutions by Gas, - Liquid, - and Solid - Phase Distribution Procedures," Anal. Chim. Acta 25:405, 1961.
9. Lai, M. G., and Goya, H. A., "A Rapid Ion Exchange Method for the Concentration of Cobalt from Seawater," U.S. Naval Radiological Defense Laboratory, USNRDL TR-67-11, 29 Nov. 1966.
10. Koltoff, I., and O'Brien, A., J. Chem. Phys. 7, 401, 1939.
11. Polessitsky, A. and Murin, A., Compt. rend. acad. Sci. U.R.S.S. 45, 238, 1944.
12. Fisher, R., and Yates, F., "Statistical Tables: Oliver and Boyd, London, 1938.